

RFID Keyfob Pear Shape

Able ID Ltd RFID keyfobs can easily be fitted to a normal key ring. They are available with the most common ICs in 125kHz as well as in 13,56MHz.



Applications:

- Access Control
- Identification
- Time Attendance

Personalisation options:

- Ink jet printed serial number

Product specification:

Dimensions:	36 x 30 x 7mm
Weight:	7g
Material:	Polycarbonat
Colours:	Standard: grey Other available colours: red, blue, green, yellow, white, black
Surface:	opac
Humidity resistance:	IP 67
Application temp.:	- 25°C to 65°C

Available 125kHz systems:

IC Type	Memory	Mode
EM4200	8 Bytes	Read Only
EM4550	125 Bytes	R/W
Atmel Temic 5567	28 Bytes	R/W
NXP Hitag 1	256 Bytes	R/W
NXP Hitag 2	32 Bytes	R/W
NXP HitagS	64/256 Bytes	R/W

Available 13,56MHz systems:

IC Type	Memory	ISO
NXP Mifare Ultralight /C	64 Bytes	14443A
NXP Mifare MF1S20 / MF1S50 / MF1S70	256 Bytes/ 1024 Bytes/ 4096 Bytes	14443A (1-3)
NXP Mifare DESFire EV1	2 kBytes/ 4 kBytes/ 8 kBytes	14443A
NXP I-Code SLI	1024 bits	15693
LEGIC MIM256 & MIM1024	256 Bytes/ 1024 Bytes	14443A
LEGIC Advant 1024 & 2048	1024 Bytes/ 2048 Bytes	14443/15693
TI HFI - Plus	1024 byte	15693