

## RFID Keyfob BASIC

Able ID Ltd keyfobs can easily be fitted to a normal key ring. They are available with the most common ICs in 125 kHz as well as in 13.56 MHz.

### Applications:

- Access Control
- Identification
- Time Attendance



### Personalisation options:

- Ink jet printed serial number

### Product specification:

<b>Dimensions:</b>	40 x 32 x 4 mm
<b>Weight:</b>	6 g
<b>Material:</b>	ABS
<b>Colours:</b>	Standard: black Other available colours: red, blue, green, yellow, grey
<b>Surface:</b>	opaque
<b>Humidity resistance:</b>	IP 67
<b>Application temp.:</b>	-25 °C to +65 °C

### Available 125 kHz systems:

IC Type	Memory	Mode
EM4200	8 Bytes	Read Only
EM4550	125 Bytes	R/W
Atmel Temic 5567	28 Bytes	R/W
NXP Hitag 1	256 Bytes	R/W
NXP Hitag 2	32 Bytes	R/W
NXP HitagS	64/256 Bytes	R/W

### Available 13.56 MHz systems:

IC Type	Memory	ISO
NXP Mifare Ultralight /C	64 Bytes	14443A
NXP Mifare MF1S20 / MF1S50 / MF1S70	256 Bytes/ 1024 Bytes/ 4096 Bytes	14443A (1-3)
NXP Mifare DESFire EV1	2 kBytes/ 4 kBytes/ 8 kBytes	14443A
NXP I-Code SLI	1024 bits	15693
LEGIC MIM256 & MIM1024	256 Bytes/ 1024 Bytes	14443A
LEGIC Advant 1024 & 2048	1024 Bytes/ 2048 Bytes	14443/15693
TI HFI - Plus	1024 byte	15693