


# CC-71

## Embeddable Tag



### CONTENTS

1	Product description .....	2
1.1	SpecificationS .....	2
1.2	dimensions .....	3
1.3	READ RANGE .....	4
1.4	environmental SPECIFICATIONS .....	4
1.5	supported services .....	5
1.6	possible applications .....	5
2	installation instructions .....	5
3	Contacting AbleID Ltd  .....	5

## 1 PRODUCT DESCRIPTION

The patent-pending **TROI CC-71 Embeddable** RFID tag provides automatic identification and tracking capabilities never-before available in such a unique package designed for rugged or hazardous use-areas. It can withstand unprecedented high temperature (consistent temperatures of 200 degrees Centigrade), high pressure and severe environmental conditions.

### 1.1 SPECIFICATIONS

<b>Device type</b>	Passive RFID tag
<b>Air interface protocol</b>	<b>UHF:</b> EPCGlobal Class1Gen2 / ISO/IEC 18000-6C
<b>Operational frequency</b>	<b>Standard:</b> UHF (865-869 MHz (EU), 902-928 MHz (US))
<b>IC options - UHF</b>	<b>Standard:</b> Alien Higgs 3 (others on request) Optional: EM, Fujitsu, Impinj, NXP (others on request)
<b>EPC memory - UHF</b>	<b>Standard:</b> 128 bit Optional: Up to 240 bit
<b>EPC memory content</b>	Unique 96-bit number encoded
<b>Extended memory - UHF</b>	<b>Standard:</b> 512 bit
<b>TID - UHF</b>	Factory-programmed, non-changeable, unique 64-bit ID.
<b>Read range - UHF</b>	Real-world: 1 – 2 meters
<b>Size</b>	Length: 165mm Wire Diameter: 1.5mm NOTE: The wire diameter in the center 25mm chip-area is 4mm
<b>Tag cover material</b>	Polyolefin thermoplastic
<b>Tensile strength</b>	2500 psi minimum
<b>Applicable surfaces</b>	Any material
<b>Product RoHS compliant?</b>	Yes
<b>Standards compliancy</b>	ATEX-compliant


## 1.2 DIMENSIONS

**Length: 165mm**

**Wire Diameter: 1.5mm**

**NOTE:** The wire diameter in the center 25mm chip-area is **4mm**

### PLAN VIEW



### 1.3 READ RANGE

	UHF max read-range on metal with 4W ERP
<b>CC-71</b> 915 MHz test (same full range 860 – 960 MHz)	660.4 cm / 260 inches (6.63 m / 21.75 feet)

The read range listed above was obtained from a lab test environment. Actual test results may be different. Testing in actual use environments is strongly recommended.

### 1.4 ENVIRONMENTAL SPECIFICATIONS

<b>Operating temperature</b>	-50°C to +200°C*
<b>Temperature Cycling Test</b>	200 deg C, continuous for 30-days
<b>IP classification</b>	IP69K
<b>Weather resistance</b>	Excellent, including UV-resistance and sea water immersion
<b>Chemical resistance</b>	No physical or performance changes in: <ul style="list-style-type: none"> <li>- Salt water</li> <li>- NaOH (depending on concentration)</li> <li>- Sulfuric acid (depending on concentration)</li> <li>- Motor oil (tested in 168 hour exposure)</li> </ul> Generally good against: <ul style="list-style-type: none"> <li>- Most solvents</li> <li>- Most acids and bases</li> </ul>

\* **NOTE:** The RFID tag will not be functional if the CC-71 tag is left at the maximum indicated temperatures such that the internal soak temperature exceeds +80 deg C. The RFID tag itself will (resume) function between -50 deg C and +80 deg C.

## 1.5 SUPPORTED SERVICES

- Tag pre-encoding

For further details, please contact **AbleID Ltd**.

## 1.6 POSSIBLE APPLICATIONS

<b>Embeddable applications</b>	Concrete, industrial garments, molded thermoplastics, compression and injection molding, high value items, aerospace applications, military applications, etc.
--------------------------------	--

## 2 INSTALLATION INSTRUCTIONS

The **CC-71** can be embedded into mold- or assembly-processes, and can be attached by clips, bands or adhesive.

## 3 CONTACTING ABLEID LTD

For additional information and technical support contact:

### **AbleID Ltd**

Maghull Business Centre, Red Lion Building, 1 Liverpool Road North, Maghull, L31 2HB, UK.

T: +44 (0)845 474 2001

F: +44 (0)845 474 2006

E: [info@ableid.com](mailto:info@ableid.com)

W: [www.ableid.com](http://www.ableid.com)

### **ADVISORY**

Although any information, recommendations, or advice contained herein is given in good faith, **Troi LLC or AbleID Ltd** makes no warranty or guarantee, express or implied, (i) that the results described herein will be obtained under end-use conditions, or (ii) as to the effectiveness or safety of any design incorporating its products, materials, services, recommendations or advice. Except as provided in **Troi LLC or AbleID Ltd** standard conditions of sale, **Troi LLC or AbleID Ltd** and its representatives shall in no event be responsible for any loss resulting from any use of its materials, products or services described herein.