

## RFID Keyfob ABS

AbleID's Keyfobs can easily be fitted to a normal Keyring. They are available with the most common IC's in 125 KHz as well as 13.56 MHz

### Applications:

- Access Control
- Health Clubs & Lesuire Centres
- Events & exhibitions
- Cashless Payments
- Theme Parks



### Personalisation Options

- Printed customer logo (pad printing)
- Laser Engraved UID
- ongoing Serial Number

### Product specification:

<b>Dimensions:</b>	56.6 × 32 × 6 mm
<b>Weight:</b>	Approx. 8 g
<b>Material:</b>	ABS
<b>Colors:</b>	grey, orange, yellow, green, blue, black
<b>Surface:</b>	matt
<b>Protection Class:</b>	IP68

### Available 125 kHz systems:

IC Type	Memory	Mode
EM4100/4200	8 byte	Read only
EM4450/4550	125 byte	R/W
Atmel Temic 5567/5577	28 byte	R/W
NXP Hitag 1 & 2	32 byte 256 byte	R/W
NXP Hitag S256 & S2048	32 byte 256 byte	R/W

### Other IC types available on request!

### Available 13.56 MHz Systems:

IC Type	Memory	ISO
NXP Mifare Ultralight	64 byte	14443A
NXP Mifare MF1S20 / MF1S50 / MF1S70	256byte / 1024 byte / 4096 byte	14443A (1-3)
NXP Mifare DESFire EV1	2K / 4K / 8K	14443A
NXP I-Code SLI	1024 bit	15693
LEGIC MIM256 & MIM1024	256 byte 1024 byte	-
LEGIC Advant 1024 & 2048	1024 byte 2048 byte	-
TI HFI - Plus	1024 byte	-