

RFID Keyfob DROP

Able ID Ltd keyfobs can easily be fitted to a normal keyring. They are available with the most common ICs in 125 kHz as well as in 13.56 MHz.

Applications:

- Access Control
- Health Clubs & Lesuire Centres
- Events & exhibitions
- Cashless Payments
- Theme Parks



Personalisation Options

- Laser Engraved Number
- Logo Printing

Product specification:

Dimensions:	53 x 33 x 4mm
Weight:	7g
Material:	Polycarbonat
Colours:	black, blue, red, green, yellow
Surface:	white
Application temp. :	- 25°C to 65°C

Available 125kHz systems:

IC Type	Memory	Mode
EM4200	8 Bytes	Read Only
EM4550	125 Bytes	R/W
Atmel Temic 5567	28 Bytes	R/W
NXP Hitag 1	256 Bytes	R/W
NXP Hitag 2	32 Bytes	R/W
NXP HitagS	64/256 Bytes	R/W

Our Keyfob DROP is also available with UHF U-Code Gen2

Other IC types available on request!

Available 13,56MHz systems:

IC Type	Memory	ISO
NXP Mifare Ultralight /C	64 Bytes	14443A
NXP Mifare MF1S20 / MF1S50 / MF1S70	256 Bytes/ 1024 Bytes/ 4096 Bytes	14443A (1-3)
NXP Mifare DESFire EV1	2 kBytes/ 4 kBytes/ 8 kBytes	14443A
NXP I-Code SLI	1024 bits	15693
LEGIC MIM256 & MIM1024	256 Bytes/ 1024 Bytes	14443A
LEGIC Advant 1024 & 2048	1024 Bytes/ 2048 Bytes	14443/15693
TI HFI - Plus	1024 byte	15693