

## RFID Keyfob PVC

AbleID's Keyfobs can easily be fitted to a normal Keyring. They are available with the most common IC's in 125 KHz as well as 13.56 MHz

Applications:

- Access Control
- Health Clubs & Lesuire Centres
- Events & exhibitions
- Cashless Payments
- Theme Parks



Personalisation options:

- Offset Printing with customer design/logo (for both sides)
- Serial number thermo print
- Barcode

### Product specification:

<b>Material:</b>	PVC
<b>Dimensions:</b>	30 × 45 × 1.1 mm
<b>Surface:</b>	Matt
<b>Application temp. :</b>	-20 °C to +65 °C

### Available 125kHz systems:

IC Type	Memory	Mode
EM4100/4200	8 byte	Read only
EM4450/4550	125 byte	R/W
Atmel Temic 5567/5577	28 byte	R/W
NXP Hitag 1 & 2	32 byte 256 byte	R/W
NXP Hitag S256 & S2048	32 byte 256 byte	R/W

**Other IC types available on request!**

### Available 13,56MHz Systems:

IC Type	Memory	ISO
NXP Mifare Ultralight	64 byte	14443A
NXP Mifare MF1S20 / MF1S50 / MF1S70	256byte / 1024 byte / 4096 byte	14443A (1-3)
NXP Mifare DESFire EV1	2K / 4K / 8K	14443A
NXP I-Code SLI	1024 bit	15693
LEGIC MIM256 & MIM1024	256 byte 1024 byte	-
LEGIC Advant 1024 & 2048	1024 byte 2048 byte	-
TI HFI - Plus	1024 byte	-