

## RFID Keyfob Sailboat

AbleID's Keyfobs can easily be fitted to a normal Keyring. They are available with the most common IC's in 125 KHz as well as 13.56 MHz

### Applications:

- Access Control
- Health Clubs & Lesuire Centres
- Events & exhibitions
- Cashless Payments
- Theme Parks

### Personalisation Options

- Laser Engraved Number
- Logo Printing



### Product specification:

<b>Dimensions:</b>	60 x 35 x 5 mm
<b>Weight:</b>	12 g
<b>Material:</b>	Polycarbonate
<b>Colours:</b>	black, white, grey, blue, red
<b>Surface:</b>	opaque
<b>Humidity resistance:</b>	IP67
<b>Operation temperature:</b>	-25 °C to +65 °C

### Available 125 kHz systems:

IC Type	Memory	Mode
EM 4100/4200	8 bytes	Read-only
EM 4450/4550	125 bytes	R/W
Atmel Temic 5567	28 bytes	R/W
NXP Hitag 1/Hitag 2	256/32 bytes	R/W
NXP Hitag S256/S2048	32/256 bytes	R/W

### Available 13.56 MHz Systems:

IC Type	Memory	ISO
NXP Mifare Ultralight	64 bytes	14443A
NXP MF1S50/MF1S70	1024/ 4096 bytes	14443A (1-3)
NXP Mifare DESFire EV1	2/4/8 kbytes	14443A
NXP I-Code SLI	128 bytes	15693
NXP I-Code SLI-S	256 bits	15693
LEGIC MIM256/MIM1024	256/1024 bytes	—

**Other IC types available on request!**