

## RFID SILICONE Modern Wristband

Ableid's Keyfobs can easily be fitted to a Normal Keyring. They are available with the Most common IC's in 125 KHz as well as 13.56 MHz

### Material: Silicone

Dimensions (inner diam.)

- Ø 70 mm
- Ø 65 mm
- Ø 60 mm
- Ø 50 mm



**Colours:** Light Blue, Pink, Green, Black

### Personalisation Options

- Serial number
- Printed logo (1 colour)
- Embossing/Debossing

### Applications:

- Access Control
- Health Clubs & Leisure Centers
- Events & exhibitions
- Cashless Payments
- Theme Parks

Product Specification:

Available Sizes:	210 mm / ø 70 mm, 26 mm width, 9 mm thickness 195 mm / ø 65 mm, 26 mm width, 5 mm thickness 180 mm / ø 60 mm, 26 mm width, 5 mm thickness 152 mm / ø 50 mm, 26 mm width, 5 mm thickness
Material:	Silicone, Opaque
Available Colours:	Light Blue, Pink, Green, White
Protection Class:	IP68
Assembly:	Injection
Operating Temperature:	-25 °C to +85 °C
RoHS	Compliant

Available 125 kHz systems:

IC Type	Memory	Mode
EM 4200	8 bytes	Read-only
EM 4550	125 bytes	R/W
Atmel Temic 5567	28 bytes	R/W
NXP Hitag 1 / Hitag 2	256 / 32 bytes	R/W
NXP Hitag S256 / S2048	32 / 256 bytes	R/W

Available 13.56 MHz Systems:

IC Type	Memory	ISO
NXP Mifare Ultralight	64 bytes	14443A
NXP Mifare MF1S50 / MF1S70	1024 / 4096 bytes	14443A (1-3)
NXP Mifare DESFire EV1	2 / 4 / 8 kbytes	14443A
NXP I-Code SLI	64 bytes	15693
NXP I-Code SLI-S	256 bytes	15693
LEGIC MIM256 / MIM1024	256 / 1024 bytes	14443A
TI Tag-it HFI Plus	128 bytes	15693