

## Product Description


The patent-pending **TROI FT-1007 Tie-Wrap** RFID tag provides automatic identification and tracking capabilities never-before available in such a unique package designed for rugged or hazardous use-areas.

The plastic-covered tag is molded onto a tie-wrap and is designed to be mounted to any metallic surface by securing the tie-wrap around any pipe or round metal object. It can withstand unprecedented high temperature (consistent temperatures of 150 degrees Centigrade), high pressure and severe environmental conditions.


### 1.1 SPECIFICATIONS

<b>Device type</b>	Passive RFID tag
<b>Air interface protocol</b>	<b>UHF:</b> EPCGlobal Class1Gen2 / ISO/IEC 18000-6C
<b>Operational frequency</b>	<b>Standard:</b> UHF (865-869 MHz (EU), 902-928 MHz (US))
<b>IC options - UHF</b>	<b>Standard:</b> Alien Higgs 3 (others on request) Optional: EM, Fujitsu, Impinj, NXP (others on request)
<b>EPC memory - UHF</b>	<b>Standard:</b> 128 bit Optional: Up to 240 bit
<b>EPC memory content</b>	Unique 96-bit number encoded
<b>Extended memory - UHF</b>	<b>Standard:</b> 512 bit
<b>TID - UHF</b>	Factory-programmed, non-changeable, unique 64-bit ID.
<b>Read range - UHF</b>	Real-world: 1 – 2 meters
<b>Size</b>	<b>Standard</b> tie length: 11 inches Tie material can be nylon or metal; contact us for additional lengths
<b>Tag material</b>	Polyolefin thermoplastic
<b>Tensile strength</b>	2500 psi minimum
<b>Applicable surfaces</b>	Any material
<b>Product RoHS compliant?</b>	Yes
<b>Standards compliancy</b>	ATEX-compliant

*Balance of page left blank*

**Dimensions**  Standard Tie Length = 280 mm (11 inches)  
Other lengths and tie materials available – contact us.

**SIDE VIEW**



## Read Range

	UHF max read-range on metal with 4W ERP
<b>FT-1007</b> (915 MHz)	660.4 cm / 260 inches (6.63 m / 21.75 feet)

\*The read range listed above was obtained from a lab test environment **using an FCC (US) Reader, test results may be different for an ETSI (EU) reader.** Actual test results may be different. Testing in actual use environments is strongly recommended.

## 1.2 ENVIRONMENTAL SPECIFICATIONS

<b>Operating temperature</b>	-50°C to +100°C*
<b>Temperature Cycling Test</b>	150 deg C, continuous for 30-days
<b>IP classification</b>	IP69K
<b>Weather resistance</b>	Excellent, including UV-resistance and sea water immersion
<b>Chemical resistance</b>	No physical or performance changes in: <ul style="list-style-type: none"> <li>- Salt water</li> <li>- NaOH (depending on concentration)</li> <li>- Sulfuric acid (depending on concentration)</li> <li>- Motor oil (tested in 168 hour exposure)</li> </ul> Generally good against: <ul style="list-style-type: none"> <li>- Most solvents</li> <li>- Most acids and bases</li> </ul>

\* **NOTE:** The RFID tag will not be functional if the tag is left at the maximum indicated temperatures such that the internal soak temperature exceeds +80 deg C. The RFID tag itself will (resume) function between -50 deg C and +80 deg C.

### 1.3 SUPPORTED SERVICES

- Tag pre-encoding

For further details, please contact [AbleID Ltd.](#)

### 1.4 POSSIBLE APPLICATIONS

<b>Any surface</b>	Returnable containers, canisters, pallets, pipes, high value items, aerospace applications, military applications, etc.
--------------------	---

### Installation Instructions

Wrap the tie-wrap around the surface and firmly pull the tie-wrap to secure the tag – done!



## 2 CONTACTING ABLEID LTD

For additional information and technical support contact:

### **AbleID Ltd**

Maghull Business Centre, Red Lion Building, 1 Liverpool Road North, Maghull, L31 2HB, UK.

T: +44 (0)845 474 2001

F: +44 (0)845 474 2006

E: [info@ableid.com](mailto:info@ableid.com)

W: [www.ableid.com](http://www.ableid.com)

### **ADVISORY**

Although any information, recommendations, or advice contained herein is given in good faith, **Troi LLC or AbleID Ltd** makes no warranty or guarantee, express or implied, (i) that the results described herein will be obtained under end-use conditions, or (ii) as to the effectiveness or safety of any design incorporating its products, materials, services, recommendations or advice. Except as provided in **Troi LLC or AbleID Ltd** standard conditions of sale, **Troi LLC or AbleID Ltd** and its representatives shall in no event be responsible for any loss resulting from any use of its materials, products or services described herein.