

FX-1 Micro Embeddable RFID Tag



CONTENTS

1	Product description	2
1.1	SpecificationS	2
1.2	dimensions	3
1.3	READ RANGE	4
1.4	environmental SPECIFICATIONS	4
1.5	supported services	5
1.6	possible applications	5
2	installation instructions	5
3	Contacting AbleID Ltd 	5

1 PRODUCT DESCRIPTION

The patent-pending **TROI FX-1 Micro Embeddable** RFID tag provides automatic identification and tracking capabilities never-before available in such a unique package designed for rugged or hazardous use-areas.


The plastic-molded, magnetic-based tag is designed to be mounted to any metallic surface by either using the magnet base to hold it to the surface, or drilling a hole into the material and placing it into the hole. It can withstand unprecedented high temperature (consistent temperatures of 150 degrees Centigrade), high pressure and severe environmental conditions.

1.1 SPECIFICATIONS

Device type	Passive RFID tag
Air interface protocol	UHF: EPCGlobal Class1Gen2 / ISO/IEC 18000-6C
Operational frequency	Standard: UHF (865-869 MHz (EU), 902-928 MHz (US))
IC options - UHF	Standard: Alien Higgs 3 (others on request) Optional: EM, Fujitsu, Impinj, NXP (others on request)
EPC memory - UHF	Standard: 128 bit Optional: Up to 240 bit
EPC memory content	Unique 96-bit number encoded
Extended memory - UHF	Standard: 512 bit
TID - UHF	Factory-programmed, non-changeable, unique 64-bit ID.
Read range - UHF	Real-world: 1 – 2 meters
Size	12mm Diameter, 7mm High
Tag material	Resin
Tensile strength	2500 psi minimum
Applicable surfaces	Any material
Product RoHS compliant?	Yes
Standards compliancy	ATEX-compliant

1.2 DIMENSIONS

PLAN VIEW



1.3 READ RANGE

	UHF max read-range on metal with 4W ERP
FX-1 (915 MHz)	660.4 cm / 260 inches (6.63 m / 21.75 feet)

*The read range listed above was obtained from a lab test environment **using an FCC (US) Reader, test results may be different for an ETSI (EU) reader.** Actual test results may be different. Testing in actual use environments is strongly recommended.

1.4 ENVIRONMENTAL SPECIFICATIONS

Operating temperature	-50°C to +150°C*
Temperature Cycling Test	150 deg C, continuous for 30-days
IP classification	IP68K
Weather resistance	Excellent, including UV-resistance and sea water immersion
Chemical resistance	No physical or performance changes in: <ul style="list-style-type: none"> - Salt water - NaOH (depending on concentration) - Sulfuric acid (depending on concentration) - Motor oil (tested in 168 hour exposure) Generally good against: <ul style="list-style-type: none"> - Most solvents - Most acids and bases

* **NOTE:** The RFID tag will not be functional if it is left at the maximum indicated temperatures such that the internal soak temperature exceeds +80 deg C. The RFID tag itself will (resume) function between -50 deg C and +80 deg C.

1.5 SUPPORTED SERVICES

- Tag pre-encoding

For further details, please contact **AbleID Ltd**.

1.6 POSSIBLE APPLICATIONS

Metal surfaces	Metal returnable containers, metal canisters, metal pallets, metal pipes, high value metal items, aerospace applications, military applications, etc.
-----------------------	---

2 INSTALLATION INSTRUCTIONS

Using the magnetic base: Place the tag onto any metallic surface. (NOTE: Be aware that the tag can be “brushed off” the surface with a strong enough force).

Embedding: Drill an appropriately sized hole, place the tag into the hole using either the magnetic base to hold it, a “swedge-fit”, or an appropriate epoxy to retain the tag in the hole (**TROI**’s AP-1 Adhesive_Paint is recommended).

3 CONTACTING ABLEID LTD

For additional information and technical support contact:

AbleID Ltd

Maghull Business Centre, Red Lion Building, 1 Liverpool Road North, Maghull, L31 2HB, UK.

T: +44 (0)845 474 2001

F: +44 (0)845 474 2006

E: info@ableid.com

W: www.ableid.com

ADVISORY

Although any information, recommendations, or advice contained herein is given in good faith, **Troi LLC or AbleID Ltd** makes no warranty or guarantee, express or implied, (i) that the results described herein will be obtained under end-use conditions, or (ii) as to the effectiveness or safety of any design incorporating its products, materials, services, recommendations or advice. Except as provided in **Troi LLC or AbleID Ltd** standard conditions of sale, **Troi LLC or AbleID Ltd** and its representatives shall in no event be responsible for any loss resulting from any use of its materials, products or services described herein.